

### Product Summary

$V_{(BR)DSS}$	$R_{DS(on)TYP}$	$I_D@25^{\circ}C$
2200V	0.9Ω@18V	8.7A
	0.8Ω@20V	

### Feature

- Wide bandgap SiC MOSFET technology
- Low On-Resistance with high blocking voltage
- Low capacitances with High-Speed switching
- Low reverse recovery(Qrr)

### Application

- Switch mode power supplies
- Auxiliary power supplies
- High voltage capacitive loads

### Package




TO-247-3L

### Marking



G D S

### Circuit diagram



### Absolute maximum ratings ( $T_c=25^{\circ}C$ unless otherwise noted)

Parameter	Symbol	Test Condition	Value	Unit
Drain-Source Voltage	$V_{DSmax}$	$V_{GS} = 0V, I_D = 100\mu A$	2200	V
Gate-Source Voltage	$V_{GSmax}$	AC ( $f > 1Hz$ )	-10/+25	V
Gate-Source Voltage	$V_{GSOP}$	Static	-4/+18	V
Continuous Drain Current	$I_D$	$V_{GS} = 18V$	8.7	A
	$I_D$	$V_{GS} = 18V, T_c = 100^{\circ}C$	6	A
Pulsed Drain Current	$I_{D,pulse}$	Pulse with $t_p$ limited by $T_{jmax}$	9	A
Power Dissipation	$P_D$	$T_J = 175^{\circ}C$	94	W
Thermal Resistance (Typ)	$R_{\theta JC}$	Junction-to-Case	1.6	$^{\circ}C/W$
Junction Temperature	$T_J$		-55~ +175	$^{\circ}C$
Storage Temperature	$T_{STG}$		-55~ +175	$^{\circ}C$

### Electrical characteristics (T<sub>J</sub>=25°C, unless otherwise noted)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit	
<b>Static Characteristics</b>							
Drain-source breakdown voltage	V <sub>(BR)DSS</sub>	V <sub>GS</sub> = 0V, I <sub>D</sub> = 100μA	2200			V	
Zero gate voltage drain current	I <sub>DSS</sub>	V <sub>DS</sub> = 2200V, V <sub>GS</sub> = 0V			50	μA	
Gate-Source leakage current	I <sub>GSS</sub>	V <sub>DS</sub> = 0V, V <sub>GS</sub> = 18V			250	nA	
Gate threshold voltage	V <sub>GS(th)</sub>	V <sub>DS</sub> = V <sub>GS</sub> , I <sub>D</sub> = 0.5mA		2.8		V	
		V <sub>DS</sub> = V <sub>GS</sub> , I <sub>D</sub> = 0.5mA, T <sub>J</sub> = 175°C		2			
Drain-source on-resistance	R <sub>DS(on)</sub>	V <sub>GS</sub> = 18V, I <sub>D</sub> = 2A		0.9	1.4	Ω	
		V <sub>GS</sub> = 20V, I <sub>D</sub> = 2A		0.8			
		V <sub>GS</sub> = 18V, I <sub>D</sub> = 2A, T <sub>J</sub> = 175°C		2.05			
		V <sub>GS</sub> = 20V, I <sub>D</sub> = 2A, T <sub>J</sub> = 175°C		2			
Transconductance	g <sub>fs</sub>	V <sub>GS</sub> = 18V, I <sub>D</sub> = 2A		1		S	
		V <sub>GS</sub> = 18V, I <sub>D</sub> = 2A, T <sub>J</sub> = 175°C		0.8			
<b>Dynamic characteristics</b>							
Input Capacitance	C <sub>iss</sub>	V <sub>DS</sub> = 1000V, V <sub>GS</sub> = 0V V <sub>AC</sub> = 25mV, f = 1MHz		168		pF	
Output Capacitance	C <sub>oss</sub>			13			
Reverse Transfer Capacitance	C <sub>rss</sub>			2.7			
Total Gate Charge	Q <sub>g</sub>	V <sub>DS</sub> = 1200V, V <sub>GS</sub> = -4V/18V I <sub>D</sub> = 2A		15		nC	
Gate-Source Charge	Q <sub>gs</sub>			1.7			
Gate-Drain Charge	Q <sub>gd</sub>			9			
Internal Gate Resistance	R <sub>G(int)</sub>	V <sub>AC</sub> = 25mV, f = 1MHz		6		Ω	
Turn-on delay time	t <sub>d(on)</sub>	V <sub>DS</sub> = 1000V, V <sub>GS</sub> = -4V/+18V I <sub>D</sub> = 2A, R <sub>G(ext)</sub> = 5Ω, L = 500μH		3		nS	
Turn-on rise time	t <sub>r</sub>			13			
Turn-off delay time	t <sub>d(off)</sub>			10			
Turn-off fall time	t <sub>f</sub>			53			
Turn-on Switching Energy	E <sub>on</sub>				47		μJ
Turn-off Switching Energy	E <sub>off</sub>				23		
Total switching energy	E <sub>tot</sub>				70		
<b>Source-Drain Diode characteristics</b>							
Diode Forward Current	I <sub>S</sub>	V <sub>GS</sub> = -4V, T <sub>C</sub> = 25°C		8		A	
Diode Forward voltage	V <sub>SD</sub>	V <sub>GS</sub> = -4V, I <sub>SD</sub> = 1A		3.7		V	
		V <sub>GS</sub> = -4V, I <sub>SD</sub> = 1A, T <sub>J</sub> = 175°C		3.3			
Reverse Recovery Time	T <sub>rr</sub>	V <sub>GS</sub> = -4V, I <sub>SD</sub> = 2A, V <sub>R</sub> = 1000V dif/dt = 600 A/μs		40		nS	
Reverse Recovery Charge	Q <sub>rr</sub>			81		nC	
Peak Reverse Recovery Current	I <sub>rrm</sub>			3		A	

## Typical Characteristics




Figure 1. Output characteristics at  $T_j=25^\circ\text{C}$




Figure 2. Output characteristics at  $T_j=175^\circ\text{C}$




Figure 3. Normalized On-Resistance vs. Temperature




Figure 4. On-Resistance vs. Drain current for Various Temperature




Figure 5. On-Resistance vs. Temperature for Various Gate Voltage




Figure 6. Transfer Characteristics for Various Junction Temperatures

## Typical Characteristics




Figure 7. Body Diode Characteristics at Tj=25°C




Figure 8. Body Diode Characteristics at Tj=175°C




Figure 9. Threshold Voltage vs. Temperature




Figure 10 Gate Charge Characteristics




Figure 11. 3rd Quadrant Characteristic at Tj=25°C




Figure 12. 3rd Quadrant Characteristic at Tj=175°C

## Typical Characteristics




Figure 13. Capacitances vs. Drain-Source Voltage (0 – 1000V)




Figure 14. Continuous Drain Current Derating vs Case Temperature




Figure 15. Transient Thermal Impedance (Junction – Case)




Figure 16. Maximum Power Dissipation Derating vs. Case Temperature




Figure 17. Output Capacitor Stored Energy




Figure 18. Safe Operating Area

## Typical Characteristics




Figure 19. Clamped Inductive Switching Energy vs. Drain Current ( $V_{DD} = 800\text{V}$ )




Figure 20. Clamped Inductive Switching Energy vs. Drain Current ( $V_{DD} = 1000\text{V}$ )




Figure 21. Clamped Inductive Switching Energy vs.  $R_{G(\text{ext})}$





Figure 22. Switching Times vs.  $R_{G(\text{ext})}$

### TO-247-3L Package Information



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	4.830	5.210	0.190	0.205
A1	2.290	2.550	0.090	0.100
A2	1.500	2.490	0.059	0.098
b	1.120	1.330	0.044	0.052
b1	1.120	1.280	0.044	0.050
b2	1.910	2.390	0.075	0.094
b3	1.910	2.340	0.075	0.092
b4	2.870	3.220	0.113	0.127
b5	2.870	3.180	0.113	0.125
c	0.550	0.690	0.022	0.027
c1	0.550	0.650	0.022	0.026
D	20.800	21.100	0.819	0.831
D1	16.250	17.650	0.640	0.695
D2	0.510	1.350	0.020	0.053
E	15.750	16.130	0.620	0.635
E1	13.460	14.160	0.530	0.557
E2	4.320	5.490	0.170	0.216
e	5.440 BSC		0.214 BSC	
L	19.810	20.320	0.780	0.800
L1	4.100	4.400	0.161	0.173
ΦP	3.560	3.650	0.140	0.144
ΦP1	7.190 REF.		0.283 REF.	
Q	5.390	6.200	0.212	0.244
S	6.040	6.300	0.238	0.248