

Product Summary

$V_{(BR)DSS}$	$R_{DS(on)MAX}$	I_D
-40V	7.5mΩ@-10V	-60A
	10.5mΩ@-4.5V	


Feature

- Split gate trench MOSFET technology
- Low $R_{DS(on)}$ & FOM
- Excellent stability and uniformity
- Suffix "-Q1" for AEC-Q101

Application


- Power management
- Portable equipment

Package




PDFN5*6-8L

Circuit diagram



Marking



Absolute maximum ratings (T_A=25°C unless otherwise noted)

Parameter	Symbol	Value	Unit
Drain-Source Voltage	V _{DS}	-40	V
Gate-Source Voltage	V _{GS}	±25	V
Continuous Drain Current (T _c =25°C)	I _D	-60	A
Continuous Drain Current (T _c =100°C)	I _D (100°C)	-38	A
Pulsed Drain Current ¹⁾	I _{DM}	-240	A
Power Dissipation ³⁾	P _D	2.5	W
Thermal Resistance, Junction-to-Ambient ⁴⁾	R _{θJA}	50	°C/W
Single pulse avalanche energy ²⁾	E _{AS}	400	mJ
Junction Temperature	T _J	150	°C
Storage Temperature	T _{STG}	-55 ~ +150	°C

Electrical characteristics (T_J=25 °C, unless otherwise noted)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Static Characteristics						
Drain-source breakdown voltage	V _{(BR)DSS}	V _{GS} = 0V, I _D = -250μA	-40			V
Zero gate voltage drain current	I _{DSS}	V _{DS} = -40V, V _{GS} = 0V			-1	μA
Gate-body leakage current	I _{GSS}	V _{GS} = ±25V, V _{DS} = 0V			±100	nA
Gate threshold voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = -250μA	-1.2	-1.7	-2.5	V
Drain-source on-resistance	R _{DS(on)}	V _{GS} = -10V, I _D = -30A		5.5	7.5	mΩ
		V _{GS} = -10V, I _D = -20A		5.5	7.5	mΩ
		V _{GS} = -4.5V, I _D = -20A		7.5	10.5	mΩ
Dynamic characteristics⁵⁾						
Input Capacitance	C _{iss}	V _{DS} = -20V, V _{GS} = 0V, f = 1MHz		4600		pF
Output Capacitance	C _{oss}			490		
Reverse Transfer Capacitance	C _{rss}			470		
Total Gate Charge	Q _g	V _{DS} = -20V, V _{GS} = -10V, I _D = -30A		99		nC
Gate-Source Charge	Q _{gs}			14		
Gate-Drain Charge	Q _{gd}			22		
Turn-on delay time	t _{d(on)}	V _{DD} = -20V, V _{GS} = -10V, I _D = -30A, R _{GEN} = 3Ω		11		nS
Turn-on rise time	t _r			52		
Turn-off delay time	t _{d(off)}			331		
Turn-off fall time	t _f			185		
Source-Drain Diode characteristics						
Diode Forward Current	I _S				-60	A
Diode Forward voltage	V _{SD}	V _{GS} = 0V, I _S = -30A			-1.2	V
Reverse Recovery Time	t _{rr}	I _F = -30A, di/dt = 100A/μs		16		nS
Reverse Recovery Charge	Q _{rr}			16		nC

Notes:

- 1) Repetitive rating; pulse width limited by max. junction temperature.
- 2) T_J=25°C, V_{DD}=-30V, V_G=-10V, R_G=25Ω, L=2mH, I_{AS}=-20A.
- 3) P_d is based on max. junction temperature, using junction-case and junction-ambient thermal resistance.
- 4) The value of R_{θJA} is measured with the device mounted on the minimum recommend pad size, in the still air environment with T_A = 25°C. The maximum allowed junction temperature of 150°C. The value in any given application depends on the user's specific board design.
- 5) Guaranteed by design, not subject to production testing.



Typical Characteristics




Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. Capacitance Characteristics




Figure 4. Gate Charge




Figure 5. On-Resistance vs Gate to Source Voltage




Figure 6. Normalized On-Resistance

Typical Characteristics




Figure 7. RDS(on) VS Drain Current




Figure 8. Forward characteristics of reverse diode




Figure 9. Normalized breakdown voltage




Figure 10. Normalized Threshold voltage




Figure 11. Current dissipation




Figure 12. Power dissipation

Typical Characteristics




Figure 13. Maximum Transient Thermal Impedance





Figure 14. Safe Operation Area

PDFN5*6-8L Package Information


Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	1.000	1.200	0.039	0.047
A1	0.254 BSC		0.010 BSC	
A2	0.000	0.100	0.000	0.004
D	5.150	5.550	0.203	0.219
E	5.950	6.350	0.234	0.250
D1	3.910	4.320	0.154	0.170
E1	3.520	3.920	0.139	0.154
D2	5.000	5.400	0.197	0.213
E2	5.660	6.060	0.223	0.239
b	0.310	0.510	0.012	0.020
e	1.270 BSC		0.050 BSC	
L1	0.560	0.760	0.022	0.030
L2	0.500 BSC		0.020 BSC	