

Product Summary

$V_{(BR)DSS}$	$R_{DS(on)MAX}$	I_D
60V	6.3mΩ@10V	60A


Feature

- Excellent package for heat dissipation
- High density cell design for low $R_{DS(on)}$

Application


- Power switching application
- Uninterruptible power supply
- DC-DC converter

Package




PDFN5*6-8L

Circuit diagram



Marking



Absolute maximum ratings ($T_a=25^{\circ}\text{C}$ unless otherwise noted)

Parameter	Symbol	Value	Unit
Drain-Source Voltage	V_{DS}	60	V
Gate-Source Voltage	V_{GS}	± 20	V
Continuous Drain Current ^{1,2)} ($T_C = 25^{\circ}\text{C}$)	I_D	60	A
Continuous Drain Current ^{1,2)} ($T_C = 100^{\circ}\text{C}$)	$I_D(100^{\circ}\text{C})$	42	A
Pulsed Drain Current	I_{DM}	240	A
Power Dissipation ^{1,2)} ($T_C = 25^{\circ}\text{C}$)	P_D	93.7	W
Thermal Resistance, Junction-to-Case	$R_{\theta JC}$	1.6	$^{\circ}\text{C/W}$
Single pulse avalanche energy ³⁾	E_{AS}	121	mJ
Junction Temperature	T_J	175	$^{\circ}\text{C}$
Storage Temperature	T_{STG}	-55 ~ +175	$^{\circ}\text{C}$

Electrical characteristics ($T_J=25^{\circ}\text{C}$, unless otherwise noted)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Static Characteristics						
Drain-source breakdown voltage	$V_{(BR)DSS}$	$V_{GS} = 0V, I_D = 250\mu A$	60			V
Zero gate voltage drain current	I_{DSS}	$V_{DS} = 48V, V_{GS} = 0V$			1	μA
Gate-body leakage current	I_{GSS}	$V_{GS} = \pm 20V, V_{DS} = 0V$			± 100	nA
Gate threshold voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = 250\mu A$	2.0	3.0	4.0	V
Drain-source on-resistance	$R_{DS(on)}$	$V_{GS} = 10V, I_D = 40A$		4.8	6.3	m Ω
Gate Resistance	R_G	f = 1MHz		1.5		Ω
Dynamic characteristics ⁴⁾						
Input Capacitance	C_{iss}	$V_{DS} = 30V, V_{GS} = 0V, f = 1MHz$		1529		pF
Output Capacitance	C_{oss}			460		
Reverse Transfer Capacitance	C_{rss}			16		
Total Gate Charge	Q_g	$V_{DS} = 30V, V_{GS} = 10V, I_D = 37.5A$		25.5		nC
Gate-Source Charge	Q_{gs}			6		
Gate-Drain Charge	Q_{gd}			14		
Turn-on delay time	$t_{d(on)}$	$V_{DS} = 30V, V_{GS} = 10V, I_D = 37.5A, R_{GEN} = 2.2\Omega$		13		nS
Turn-on rise time	t_r			50		
Turn-off delay time	$t_{d(off)}$			21.8		
Turn-off fall time	t_f			8.6		
Source-Drain Diode characteristics						
Diode Forward voltage	V_{SD}	$V_{GS} = 0V, I_S = 40A$			1.2	V
Reverse Recovery Time	T_{rr}	$I_F = 37.5A, di/dt = 270A/\mu s, V_{GS} = 0V, V_R = 20V$		28		nS
Reverse Recovery Charge	Q_{rr}			40		nC

Notes:

- 1) The entire application environment impacts the thermal resistance values shown, they are not constants and are only valid for the particular conditions noted.
- 2) Thermal resistance from junction to soldering point (on the exposed drain pad).
- 3) $T_J = 25^{\circ}\text{C}, V_G = 10\text{V}, R_G = 25\Omega, L = 0.5\text{mH}, I_{AS} = 22\text{A}$.
- 4) Guaranteed by design, not subject to production.

Typical Characteristics




Figure 1. Output Characteristics; typical values




Figure 2. Transfer Characteristics; typical values




Figure 3. Capacitance Characteristics; typical values




Figure 4. Gate Charge; typical values




Figure 5. On-Resistance vs. Gate to Source Voltage; typical values




Figure 6. Normalized On-Resistance

Typical Characteristics




Figure 7. $R_{DS(on)}$ vs. Drain Current; typical values




Figure 8. Forward characteristics of reverse diode; typical values




Figure 9. Normalized breakdown voltage




Figure 10. Normalized Threshold voltage




Figure 11. Current dissipation




Figure 12. Power dissipation

Typical Characteristics




Figure 13. Maximum Transient Thermal Impedance





Figure 14. Safe Operation Area

PDFN5*6-8L Package Information



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
D	5.150	5.550	0.203	0.219
E	5.950	6.350	0.234	0.250
A	1.000	1.200	0.039	0.047
A1	0.254 BSC.		0.010 BSC.	
A2	-	0.100	-	0.004
D1	1.500	1.900	0.059	0.075
E1	3.520	3.920	0.139	0.154
D2	5.000	5.400	0.197	0.213
E2	5.660	6.060	0.223	0.239
E3	0.254 REF.		0.010 REF.	
E4	0.210 REF.		0.008 REF.	
L1	0.560	0.760	0.022	0.030
L2	0.500 BSC.		0.020 BSC.	
b	0.310	0.510	0.012	0.020
e	1.270 BSC.		0.050 BSC.	