

Product Summary

$V_{(BR)DSS}$	$R_{DS(on)MAX}$	I_D
60V	9.5mΩ@10V	50A
	14mΩ@4.5V	

Feature

- Excellent package for heat dissipation
- High density cell design for low $R_{DS(ON)}$


Application

- DC/DC Converter
- Power switching application
- Uninterruptible power supply


Package




PDFN5*6-8L



Circuit diagram



Marking



Absolute maximum ratings ($T_J=25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Value	Unit
Drain-Source Voltage	V_{DS}	60	V
Gate-Source Voltage	V_{GS}	± 20	V
Continuous Drain Current ^{1,2)} ($T_C = 25^\circ\text{C}$)	I_D	50	A
Continuous Drain Current ^{1,2)} ($T_C = 100^\circ\text{C}$)	$I_D (100^\circ\text{C})$	31	A
Pulsed Drain Current ($T_C = 25^\circ\text{C}$, $t_P = 100\mu\text{s}$)	I_{DM}	180	A
Single Pulse Avalanche Energy ³⁾	E_{AS}	42.25	mJ
Power Dissipation ^{1,2)} ($T_C = 25^\circ\text{C}$)	P_D	50	W
Thermal Resistance Junction to Case	$R_{\theta JC}$	2.5	$^\circ\text{C}/\text{W}$
Operating Junction Temperature	T_J	-55 ~ +150	$^\circ\text{C}$
Storage Temperature Range	T_{STG}	-55 ~ +150	$^\circ\text{C}$

Electrical characteristics ($T_J=25^\circ\text{C}$, unless otherwise noted)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Static Characteristics						
Drain-source breakdown voltage	$V_{(BR)DSS}$	$V_{GS} = 0\text{V}$, $I_D = 250\mu\text{A}$	60			V
Zero gate voltage drain current	I_{DSS}	$V_{DS} = 60\text{V}$, $V_{GS} = 0\text{V}$			1	μA
Gate-body leakage current	I_{GSS}	$V_{DS} = 0\text{V}$, $V_{GS} = \pm 20\text{V}$			± 100	nA
Gate threshold voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}$, $I_D = 250\mu\text{A}$	1.3	1.8	2.3	V
Drain-source on-resistance	$R_{DS(on)}$	$V_{GS} = 10\text{V}$, $I_D = 25\text{A}$		7.4	9.5	m Ω
		$V_{GS} = 4.5\text{V}$, $I_D = 13\text{A}$		10.7	14	
Dynamic characteristics⁴⁾						
Input Capacitance	C_{iss}	$V_{DS} = 30\text{V}$, $V_{GS} = 0\text{V}$, $f = 1\text{MHz}$		875		pF
Output Capacitance	C_{oss}			300		
Reverse Transfer Capacitance	C_{rss}			15.5		
Total Gate Charge	Q_g	$V_{DS} = 30\text{V}$, $V_{GS} = 10\text{V}$, $I_D = 23\text{A}$		15.2		nC
Gate-Source Charge	Q_{gs}			3.2		
Gate-Drain Charge	Q_{gd}			3.4		
Turn-on delay time	$t_{d(on)}$	$V_{DS} = 30\text{V}$, $V_{GS} = 10\text{V}$, $I_D = 23\text{A}$ $R_G = 2.7\Omega$		9		nS
Turn-on rise time	t_r			51		
Turn-off delay time	$t_{d(off)}$			20		
Turn-off fall time	t_f			6		
Source-Drain Diode characteristics						
Diode Forward Current	I_S				50	A
Diode Forward voltage	V_{SD}	$V_{GS} = 0\text{V}$, $I_S = 25\text{A}$			1.2	V
Reverse Recovery Time	T_{rr}	$I_F = 23\text{A}$, $di/dt = -100\text{A}/\mu\text{s}$		17.3		nS
Reverse Recovery Charge	Q_{rr}			9		nC

Notes:

- 1) The entire application environment impacts the thermal resistance values shown, they are not constants and are only valid for the particular conditions noted.
- 2) Thermal resistance from junction to soldering point (on the exposed drain pad).
- 3) EAS condition: $V_G = 10\text{V}$, $R_G = 25\Omega$, $L = 0.5\text{mH}$, $I_{AS} = 13\text{A}$.
- 4) Guaranteed by design, not subject to production testing.

Typical Characteristics




Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. Capacitance Characteristics




Figure 4. Gate Charge




Figure 5. On-Resistance vs Gate to Source Voltage




Figure 6. Normalized On-Resistance

Typical Characteristics




Figure 7. $R_{DS(on)}$ VS Drain Current




Figure 8. Forward characteristics of reverse diode




Figure 9. Normalized breakdown voltage




Figure 10. Normalized Threshold voltage




Figure 11. Current dissipation




Figure 12. Power dissipation

Typical Characteristics




Figure 13. Maximum Transient Thermal Impedance





Figure 14. Safe Operation Area

PDFN5*6-8L Package Information



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
D	5.150	5.550	0.203	0.219
E	5.950	6.350	0.234	0.250
A	1.000	1.200	0.039	0.047
A1	0.254 BSC.		0.010 BSC.	
A2	0.000	0.100	0.000	0.004
D1	3.920	4.320	0.154	0.170
E1	3.520	3.920	0.139	0.154
D2	5.000	5.400	0.197	0.213
E2	5.660	6.060	0.223	0.239
E3	0.254 REF.		0.010 REF.	
E4	0.210 REF.		0.008 REF.	
L1	0.560	0.760	0.022	0.030
L2	0.500 BSC.		0.020 BSC.	
b	0.310	0.510	0.012	0.020
e	1.270 BSC.		0.050 BSC.	