

Product Summary

$V_{(BR)CES}$	$V_{CE(SAT)TYP}$	$I_C(100^{\circ}C)$
650V	1.6V@15V	80A


Feature

- High speed smooth switching device for hard & soft switching
- Maximum junction temperature 175°C
- Positive temperature coefficient
- High ruggedness, temperature stable
- High short circuit capability (5us)

Application


- Resonant converters
- Uninterruptible power supplies
- Mid to high range switching frequency converters

Package




TO-247AB

Circuit diagram



Marking



Absolute maximum ratings ($T_C=25^{\circ}\text{C}$ unless otherwise noted)

Parameter	Symbol	Value	Unit
Collector-Emitter Voltage	V_{CES}	650	V
Continuous Gate- Emitter Voltage	V_{GE}	± 20	V
Transient Gate-Emitter Voltage ($t_p \leq 10\mu\text{s}, D < 0.01$)	V_{GE}	± 30	V
Collector Current, limited by T_{jmax}	I_C	85	A
Collector Current, limited by T_{jmax} ($T_C = 100^{\circ}\text{C}$)	$I_C(100^{\circ}\text{C})$	80	A
Pulsed Collector Current, t_p limited by T_{jmax} ($V_{GE} = 15\text{V}$)	I_{CM}	300	A
Diode Continuous Forward Current, limited by T_{jmax}	I_F	85	A
Diode Continuous Forward Current, limited by T_{jmax} ($T_C = 100^{\circ}\text{C}$)	$I_F(100^{\circ}\text{C})$	80	A
Diode Pulsed Current, t_p limited by T_{jmax}	I_{Fpuls}	300	A
Turn off Safe Operating Area ($V_{CE} \leq 650\text{V}, T_J \leq 150^{\circ}\text{C}$)	-	300	A
Short Circuit Withstand Time ($V_{CE} \leq 650\text{V}, V_{GE} = 15\text{V}, V_{CC} = 400\text{V}$)	T_{SC}	5	μs
Power Dissipation ($T_J = 175^{\circ}\text{C}$)	P_D	469	W
Thermal Resistance, Junction to case for Diode	$R_{\theta JC}$	0.41	$^{\circ}\text{C/W}$
Thermal Resistance, Junction to case for IGBT	$R_{\theta JC}$	0.32	$^{\circ}\text{C/W}$
Operating junction temperature range	T_J	$-40 \sim +175$	$^{\circ}\text{C}$
Storage Temperature Range	T_{STG}	$-55 \sim +150$	$^{\circ}\text{C}$

Electrical characteristics of the IGBT ($T_J=25^{\circ}\text{C}$ unless otherwise noted)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Static Characteristics						
Collector-Emitter Breakdown Voltage	$V_{(BR)CES}$	$V_{GE}=0V, I_C=250\mu A$	650			V
Collector-Emitter Leakage Current	I_{CES}	$V_{GE}=0V, V_{CE}=650V$			0.25	mA
		$V_{GE}=0V, V_{CE}=650V, T_J=150^{\circ}C$			3	
Gate to Emitter Leakage Current	I_{GES}	$V_{GE}=\pm 20V, V_{CE}=0V$			100	nA
Gate Threshold Voltage	$V_{GE(th)}$	$V_{GE}=V_{CE}, I_C=0.25mA$	4	5.5	7	V
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$V_{GE}=15V, I_C=75A$	1.3	1.6	1.9	V
		$V_{GE}=15V, I_C=75A, T_J=125^{\circ}C$		1.75		
		$V_{GE}=15V, I_C=75A, T_J=150^{\circ}C$		1.8		
Dynamic characteristics						
Input Capacitance	C_{ies}	$V_{CE}=30V, V_{GE}=0V, f=1MHz$		4.2		nF
Reverse Transfer Capacitance	C_{res}			0.08		
Total Gate Charge	Q_g	$V_{CC}=400V, V_{GE}=15V, I_C=75A$		0.23		μC
Short Circuit Collector Current	I_{SC}	$V_{GE}=15V, V_{CC}=400V, t_{sc}\leq 5us$		464		A
Turn-on delay time	$t_{d(on)}$	$V_{CC}=400V, V_{GE}=-5V\sim 15V$ $I_C=75A, R_G=10\Omega$ Inductive load		60		nS
Turn-on rise time	t_r			102		
Turn-off delay time	$t_{d(off)}$			138		
Turn-off fall time	t_f			51		
Turn-On Energy	E_{on}			3.51		mJ
Turn-Off Energy	E_{off}			1.43		
Total Switching Energy	E_{ts}			4.94		

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Dynamic characteristics						
Turn-on delay time	$t_{d(on)}$	$V_{CC}=400V$, $V_{GE}=-5V\sim 15V$ $I_C=75A$, $R_G=10\Omega$ Inductive load $T_J=125^\circ C$		58		nS
Turn-on rise time	t_r			99		
Turn-off delay time	$t_{d(off)}$			154		
Turn-off fall time	t_f			92		
Turn-On Energy	E_{on}			3.54		mJ
Turn-Off Energy	E_{off}			1.98		
Total Switching Energy	E_{ts}			5.52		
Turn-on delay time	$t_{d(on)}$	$V_{CC}=400V$, $V_{GE}=-5V\sim 15V$ $I_C=75A$, $R_G=10\Omega$ Inductive load $T_J=150^\circ C$		55		nS
Turn-on rise time	t_r			93		
Turn-off delay time	$t_{d(off)}$			161		
Turn-off fall time	t_f			109		
Turn-On Energy	E_{on}			3.55		mJ
Turn-Off Energy	E_{off}			2.14		
Total Switching Energy	E_{ts}			5.69		

Electrical characteristics of the Diode ($T_J=25^\circ C$ unless otherwise noted)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Diode Forward Voltage	V_F	$I_F=75A$		1.65	2.1	V
		$I_F=75A$, $T_J=125^\circ C$		1.6		
		$I_F=75A$, $T_J=150^\circ C$		1.5		
Reverse Recovery Current	I_{rrm}	$V_R=400V$, $I_F=75A$ $di/dt=-720A/\mu s$		25		A
Reverse Recovery Charge	Q_{rr}			0.94		μC
Reverse Recovery Time	T_{rr}			61		nS
Reverse Recovery Energy	E_{rec}			0.09		mJ
Reverse Recovery Current	I_{rrm}	$V_R=400V$, $I_F=75A$ $di/dt=-720A/\mu s$ $T_J=125^\circ C$		38		A
Reverse Recovery Charge	Q_{rr}			2.4		μC
Reverse Recovery Time	T_{rr}			97		nS
Reverse Recovery Energy	E_{rec}			0.32		mJ
Reverse Recovery Current	I_{rrm}	$V_R=400V$, $I_F=75A$ $di/dt=-720A/\mu s$ $T_J=150^\circ C$		44		A
Reverse Recovery Charge	Q_{rr}			3.03		μC
Reverse Recovery Time	T_{rr}			112		nS
Reverse Recovery Energy	E_{rec}			0.42		mJ

Typical Characteristics




Fig1. Power dissipation as a function of case temperature ($T_j \leq 175^\circ\text{C}$)




Fig2. Collector current as a function of case temperature ($V_{ge} \geq 15\text{V}$, $T_j \leq 175^\circ\text{C}$)




Fig3. Typical output characteristic ($T_j = 25^\circ\text{C}$)




Fig4. Typical output characteristic ($T_j = 150^\circ\text{C}$)




Fig5. Typical transfer characteristic ($V_{ce} = 20\text{V}$)










Fig6. Typical collector-emitter saturation voltage as a function of junction temperature ($V_{ge} = 15\text{V}$)

Typical Characteristics



Typical Characteristics






Fig 15. IGBT Transient Thermal Impedance







Fig 16. Diode Transient Thermal Impedance



TO-247AB Package Information



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	4.800	5.200	0.189	0.205
A1	2.210	2.610	0.087	0.103
A2	1.850	2.150	0.073	0.085
b	1.000	1.400	0.039	0.055
b2	1.910	2.210	0.075	0.087
b3	2.800	3.200	0.110	0.126
C	0.500	0.700	0.020	0.028
D	20.700	21.300	0.815	0.839
D1	16.250	16.850	0.640	0.663
E	15.500	16.100	0.610	0.634
E1	13.000	13.600	0.512	0.535
E2	4.800	5.200	0.189	0.205
E3	2.300	2.700	0.091	0.106
L	19.620	20.220	0.772	0.796
L1	-	4.300	-	0.169
Φ P	3.400	3.800	0.134	0.150
Φ P1	-	7.300	-	0.287
S	6.150 TYP.		0.242 TYP.	
H1	5.440 TYP.		0.214 TYP.	