

Features


- Low reverse current
- Good surge current capability
- Low capacitive charge
- No reverse recovery current

V_{RRM}	=	650	V
$I_F (T_C = 162^\circ\text{C})$	=	6	A
Q_C	=	18	nC

Benefits

- System efficiency improvement over Si diodes
- Higher switching frequency
- Increased power density
- Essentially no switching losses

Package



TO-220-2

Applications

- Switch mode power supplies (SMPS)
- Uninterruptible power supplies
- On Board Charger
- UPS



Part Number	Package	Marking
ASZD006065A	TO-220-2	ASZD006065A

Maximum Ratings ($T_C=25^\circ\text{C}$ unless otherwise specified)

Symbol	Parameter	Test conditions	Value	Unit
V_{RRM}	Repetitive peak reverse voltage		650	V
V_{RSM}	Non-repetitive peak reverse voltage		650	V
I_F	Continuous forward current	$T_C=25^\circ\text{C}$	23	A
		$T_C=135^\circ\text{C}$	12	
		$T_C=162^\circ\text{C}$	6	
I_{FRM}	Repetitive forward surge current	$T_C=25^\circ\text{C}$, $t_p=10\text{ms}$, Half Sine Pulse	28	A
		$T_C=110^\circ\text{C}$, $t_p=10\text{ms}$, Half Sine Pulse	17	
I_{FSM}	Non-Repetitive forward surge current	$T_C=25^\circ\text{C}$, $t_p=10\text{ms}$, Half Sine Pulse	48	A
		$T_C=110^\circ\text{C}$, $t_p=10\text{ms}$, Half Sine Pulse	43	
$\int i^2 dt$	i^2t value	$T_C=25^\circ\text{C}$, $t_p=10\text{ms}$, Half Sine Pulse	11.4	A^2S
		$T_C=110^\circ\text{C}$, $t_p=10\text{ms}$, Half Sine Pulse	9.1	
P_{tot}	Power dissipation	$T_C=25^\circ\text{C}$	71	W
		$T_C=110^\circ\text{C}$	30	
T_j	Operating junction temperature		-55~+175	$^\circ\text{C}$
T_{stg}	Storage temperature		-55~+175	$^\circ\text{C}$

Electrical Characteristics ($T_j=25^\circ\text{C}$ unless otherwise specified)

Static Characteristics

Symbol	Parameter	Test conditions	Value			Unit
			Min.	Typ.	Max.	
V_{DC}	DC blocking voltage	$T_j=25^\circ\text{C}$	650			V
V_F	Diode forward voltage	$I_F=6\text{A}$ $T_j=25^\circ\text{C}$ $I_F=6\text{A}$ $T_j=175^\circ\text{C}$		1.3 1.5	1.5	V
I_R	Reverse current	$V_R=650\text{V}$ $T_j=25^\circ\text{C}$ $V_R=650\text{V}$ $T_j=175^\circ\text{C}$			50 200	μA

AC Characteristics ($T_j=25^\circ\text{C}$ unless otherwise specified)

Symbol	Parameter	Test conditions	Value			Unit
			Min.	Typ.	Max.	
Q_C	Total capacitive charge	$V_R=400\text{V}$ $T_j=25^\circ\text{C}$ $Q_C = \int_0^{V_R} C(V)dV$		18		nC
C	Total capacitance	$V_R=0\text{V}$ $f=1\text{MHz}$		358		pF
		$V_R=200\text{V}$ $f=1\text{MHz}$		36		
		$V_R=400\text{V}$ $f=1\text{MHz}$		30		

Thermal Characteristics

Symbol	Parameter	Value			Unit
		Min.	Typ.	Max.	
$R_{th(jc)}$	Thermal resistance from junction to case		2.10		$^\circ\text{C}/\text{W}$

Typical Performance




Figure 1. Typical forward characteristics




Figure 2. Typical reverse current as function of reverse voltage




Figure 3. Diode forward current as function of temperature, D=duty cycle




Figure 4. Typical capacitance as function of reverse voltage, $C=f(V_R)$; $T_j=25^\circ\text{C}$




Figure 5. Typical reverse charge as function of reverse voltage




Figure 6. Power dissipation as function of case temperature

Typical Performance




Figure 7. Capacitance stored energy





Figure 8. Max. transient thermal impedance

Package Dimensions

Package TO-220-2



Symbol	Min. (mm)	Typ. (mm)	Max. (mm)
A	9.17	10.08	10.91
B	27.00	28.58	30.00
C	3.89	4.50	5.00
D	4.20	5.10	5.80
E	11.70	13.30	14.97
F	0.50	0.80	1.21