

Product Summary

$V_{(BR)DSS}$	$R_{DS(on)MAX}$	I_D
-20V	40mΩ@-4.5V	-5A
	70mΩ@-2.5V	


Feature

- Split gate trench MOSFET technology
- Extremely low switching loss
- Excellent stability and uniformity
- Low $R_{DS(on)}$ & FOM

Application


- power management
- Portable equipment

Package




SOT-23

Circuit diagram



Marking



Absolute maximum ratings (T_A=25°C unless otherwise noted)

Parameter	Symbol	Value	Unit
Drain-Source Voltage	V _{DS}	-20	V
Gate-Source Voltage	V _{GS}	±10	V
Continuous Drain Current	I _D	-5	A
Continuous Drain Current (T _A =100°C)	I _D (100°C)	-3.2	A
Pulsed Drain Current ¹⁾	I _{DM}	-30	A
Power Dissipation ²⁾	P _D	1	W
Thermal Resistance Junction to Ambient ³⁾	R _{θJA}	125	°C/W
Operating Junction Temperature	T _J	-55 ~ +150	°C
Storage Temperature	T _{STG}	-55 ~ +150	°C

Electrical characteristics (T_J=25 °C unless otherwise noted)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Static Characteristics						
Drain-source breakdown voltage	V _{(BR)DSS}	V _{GS} = 0V, I _D = -250μA	-20			V
Zero gate voltage drain current	I _{DSS}	V _{DS} = -20V, V _{GS} = 0V			-1	μA
Gate-body leakage current	I _{GSS}	V _{DS} = 0V, V _{GS} = ±10V			±10	μA
Gate threshold voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = -250μA	-0.55	-0.85	-1.25	V
Drain-source on-resistance	R _{DS(on)}	V _{GS} = -4.5V, I _D = -5A		28	40	mΩ
		V _{GS} = -2.5V, I _D = -4A		50	70	
Dynamic characteristics⁴⁾						
Input Capacitance	C _{iss}	V _{DS} = -10V, V _{GS} = 0V, f = 1MHz		540		pF
Output Capacitance	C _{oss}			120		
Reverse Transfer Capacitance	C _{rss}			100		
Total Gate Charge	Q _g	V _{DS} = -10V, V _{GS} = -10V, I _D = -5A		13		nC
Gate-Source Charge	Q _{gs}			2		
Gate-Drain Charge	Q _{gd}			2		
Turn-on delay time	t _{d(on)}	V _{DS} = -10V, V _{GS} = -10V, I _D = -5A R _G = 2.2Ω		5		nS
Turn-on rise time	t _r			47		
Turn-off delay time	t _{d(off)}			52		
Turn-off fall time	t _f			69		
Source-Drain Diode characteristics						
Diode Forward Current	I _S				-5	A
Diode Forward voltage	V _{SD}	V _{GS} = 0V, I _S = -5A			-1.2	V
Reverse Recovery Time	T _{rr}	I _F = -5A, di/dt = -100A/us		20		nS
Reverse Recovery Charge	Q _{rr}				2.5	

Notes:

- 1) Repetitive rating; pulse width limited by max. junction temperature.
- 2) P_d is based on max. junction temperature, using junction-case and junction-ambient thermal resistance.
- 3) The value of R_{θJA} is measured with the device mounted on 1 in² FR-4 board with 2oz. Copper, in the still air environment with T_A=25°C. The maximum allowed junction temperature of 150°C. The value in any given application depends on the user's specific board design.
- 4) Guaranteed by design, not subject to production testing.

Typical Characteristics




Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. Capacitance Characteristics




Figure 4. Gate Charge




Figure 5. On-Resistance vs Gate to Source Voltage




Figure 6. Normalized On-Resistance

Typical Characteristics




Figure 7. $R_{DS(on)}$ VS Drain Current




Figure 8. Forward characteristics of reverse diode




Figure 9. Normalized breakdown voltage




Figure 10. Normalized Threshold voltage




Figure 11. Current dissipation







Figure 12. Power dissipation

Typical Characteristics



SOT-23 Package Information



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.100	0.200	0.004	0.008
D	2.800	3.000	0.110	0.118
E	1.200	1.400	0.047	0.055
E1	2.250	2.550	0.089	0.100
e	0.950 TYP.		0.037 TYP.	
e1	1.800	2.000	0.071	0.079
L	0.550 REF.		0.022 REF.	
L1	0.300	0.500	0.012	0.020
θ	0°	8°	0°	8°