

Product Summary

$V_{(BR)DSS}$	$R_{DS(on)MAX}$	I_D
-30V	18mΩ@-10V	-16A
	30mΩ@-4.5V	


Feature

- Fast switching speed
- Low On-Resistance

Application


- DC-DC Converters
- Power Management

Package




PDFN3*3-8L

Circuit diagram



Marking



Absolute maximum ratings ($T_A=25^{\circ}\text{C}$ unless otherwise noted)

Parameter	Symbol	Value	Unit
Drain-Source Voltage	V_{DS}	-30	V
Gate-Source Voltage	V_{GS}	± 20	V
Continuous Drain Current ($T_C=25^{\circ}\text{C}$)	I_D	-16	A
Continuous Drain Current ($T_C=100^{\circ}\text{C}$)	$I_D (100^{\circ}\text{C})$	-10	A
Pulsed Drain Current	I_{DM}	-64	A
Single Pulse Avalanche Energy ¹⁾	E_{AS}	156	mJ
Power Dissipation ($T_C=25^{\circ}\text{C}$)	P_D	25	W
Thermal Resistance Junction to Case	$R_{\theta JC}$	5	$^{\circ}\text{C/W}$
Operating Junction Temperature	T_J	$-55 \sim +150$	$^{\circ}\text{C}$
Storage Temperature	T_{STG}	$-55 \sim +150$	$^{\circ}\text{C}$

Electrical characteristics ($T_A=25^{\circ}\text{C}$, unless otherwise noted)


Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Static Characteristics						
Drain-source breakdown voltage	$V_{(BR)DSS}$	$V_{GS}=0V, I_D=-250\mu A$	-30			V
Zero gate voltage drain current	I_{DSS}	$V_{DS}=-24V, V_{GS}=0V, T_J=25^{\circ}C$			-1	μA
Gate-body leakage current	I_{GSS}	$V_{GS}=\pm 20V, V_{DS}=0V$			± 100	nA
Gate threshold voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=-250\mu A$	-1.2	-1.6	-2.5	V
Drain-source on-resistance	$R_{DS(on)}$	$V_{GS}=-10V, I_D=-20A$		13	18	m Ω
		$V_{GS}=-4.5V, I_D=-15A$		22	30	
Dynamic characteristics ²⁾						
Input Capacitance	C_{iss}	$V_{DS}=-15V, V_{GS}=0V, f=1MHz$		1600		pF
Output Capacitance	C_{oss}			350		
Reverse Transfer Capacitance	C_{rss}			300		
Total Gate Charge	Q_g	$V_{DS}=-15V, V_{GS}=-10V$ $I_D=-10A$		30		nC
Gate-Source Charge	Q_{gs}			5.5		
Gate-Drain Charge	Q_{gd}			8		
Turn-on delay time	$t_{d(on)}$	$V_{DS}=-15V, V_{GS}=-10V$ $I_D=-10A, R_G=3\Omega$		10		nS
Turn-on rise time	t_r			60		
Turn-off delay time	$t_{d(off)}$			52		
Turn-off fall time	t_f			70		
Source-Drain Diode characteristics						
Diode Forward Current	I_S				-16	A
Diode Forward voltage	V_{SD}	$V_{GS}=0V, I_S=-1A, T_J=25^{\circ}C$			-1.2	V
Reverse Recovery Time	T_{rr}	$I_S=-5A, di/dt=100A/\mu s$ $T_J=25^{\circ}C$		15		nS
Reverse Recovery Charge	Q_{rr}			5		nC

Notes:


1) The EAS test condition is $V_{DD}=-15V, V_G=-10V, L=0.5mH, R_G=25\Omega$.

2) Guaranteed by design, not subject to production testing.


Typical Characteristics




Output Characteristics




Transfer Characteristics




Capacitance Characteristics



Forward characteristics of reverse diode




Current dissipation




Power dissipation


Typical Characteristics




$R_{DS(on)}$ VS Drain Current




Normalized breakdown voltage



Normalized Threshold voltage




Maximum Transient Thermal Impedance



Safe Operation Area

PDFN3*3-8L Package Information



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	0.650	0.850	0.026	0.033
A1	0.152 REF.		0.006 REF.	
A2	0.000	0.050	0.000	0.002
D	2.900	3.100	0.114	0.122
D1	2.300	2.600	0.091	0.102
E	2.900	3.100	0.114	0.122
E1	3.150	3.450	0.124	0.136
E2	1.535	1.935	0.060	0.076
b	0.200	0.400	0.008	0.016
e	0.550	0.750	0.022	0.030
L	0.300	0.500	0.012	0.020
L1	0.180	0.480	0.007	0.019
L2	0.000	0.100	0.000	0.004
L3	0.000	0.100	0.000	0.004
H	0.315	0.515	0.012	0.020
θ	9°	13°	9°	13°