

Note: We are enhancing our systems and you may notice duplicate entries/missing/outdated data. During this interim period, please contact our Customer Service at <https://www.ul.com/about/locations>.


Isolated Loop Circuit Protectors - Component

COMPANY

SHENZHEN ANBON SEMICONDUCTOR LTD

Building 1, Jinlixiang Industrial Zone, Fukang Community
Longhua District
Shenzhen, Guangdong 518000 China

E513355

Marking: Company name model designation, and the Recognized Component Mark 

Note: For additional marking information, refer to the [Guide Information Page](#).

Transient Voltage Suppressor, Axial Lead Type, Model(s): 12KP may be followed by -T, followed by 20, 22, 24, 26, 28, 30, 33, 36, 40, or 43, followed by A or CA

Transient Voltage Suppressor, Axial Lead Type, Model(s): 6KP may be followed by -T, followed by 20, 22, 24, 26, 28, 30, 33, 36, 40, or 43, followed by A or CA

Transient Voltage Suppressor, Surface Mount Type, Model(s): 5.0SMDJ followed by 11, 12, 13, 14, 15, 16, 17, 18, 20, 22, 24, 26, 28, 30, 33, 36, 40, 43, 45, 48, 51, 54, 58, 60, 64, 70, 75, 78, 85, 90, 100, 110, 120, 130, 150, 160, or 170, followed by A or CA

Transient Voltage Suppressor, Surface Mount Type, Model(s): P4SMA followed by 6.8, 7.5, 8.2, 9.1, 10, 11, 12, 13, 15, 16, 18, 20, 22, 24, 27, 30, 33, 36*, 39*, 43*, 47*, 51*, 56*, 62*, or 68*, followed by A or CA

Transient Voltage Suppressor, Surface Mount Type, Model(s): P6SMB followed by 6.8, 7.5, 8.2, 9.1, 10, 11, 12, 13, 15, 16, 18, 20, 22, 24, 27, 30, 33, 36, 39, 43, 47, 51, 56, 62*, 68*, 75*, or 82*, followed by A or CA

Transient Voltage Suppressor, Surface Mount Type, Model(s): SMA6J followed by 5.0, 6.0, 6.5, 7.0, 7.5, 8.0, 8.5, 9.0, 10, 11, 12, 13, 14, 15, 16, 17, 18, 20, 22, 24, 26, 28, 30, 33, 36, 40, 43, 45, 48, 51*, 54*, 58*, 60*, 64*, 70*, or 75*, followed by A or CA

Transient Voltage Suppressor, Surface Mount Type, Model(s): SMAJ followed by 5.0, 6.0, 6.5, 7.0, 7.5, 8.0, 8.5, 9.0, 10, 11, 12, 13, 14, 15, 16, 17, 18, 20, 22, 24, 26, 28, 30, 33, 36, 40, 43, 45, 48, 51, 54, 58, 60, 64, 70, 75, 78, 85, 90, 100, 110, 120, 130, 150, 160, 170, 180, 200, 220, 250, 300, 350, 400, or 440 followed by A or CA

Transient Voltage Suppressor, Surface Mount Type, Model(s): SMB10J followed by 5.0, 6.0, 6.5, 7.0, 7.5, 8.0, 8.5, 9.0, 10, 11, 12, 13, 14, 15, 16, 17, 18, 20, 22, 24, 26, 28, 30, 33, 36, 40, 43, 45, 48, 51, 54, 58, 60, 64, 70, 75*, 78*, 85*, 90*, 100*, 110*, 120*, or 130*, followed by A or CA

Transient Voltage Suppressor, Surface Mount Type, Model(s): SMBF15J followed by 5.0, 6.0, 6.5, 7.0, 7.5, 8.0, 8.5, 9.0, 10, 11, 12, 13, 14, 15, 16, 17, 18, 20, 22, 24, 26, 28, 30, 33, 36, 40, 43, 45, 48, 51, 54, 58, 60, 64, 70, 75, 78, 85, 90, 100, 110*, 120*, 130*, 150*, 160*, 170*, 180*, 190* or 200*, followed by A or CA

Transient Voltage Suppressor, Surface Mount Type, Model(s): SMBJ followed by 5.0, 6.0, 6.5, 7.0, 7.5, 8.0, 8.5, 9.0, 10, 11, 12, 13, 14, 15, 16, 17, 18, 20, 22, 24, 26, 28, 30, 33, 36, 40, 43, 45, 48, 51, 54, 58, 60, 64, 70, 75, 78, 85, 90, 100, 110, 120, 130, 150, 160, 170, 180, 190, 200, 210, 220, 250, 300, 350, 400, or 440, followed by A or CA

Transient Voltage Suppressor, Surface Mount Type, Model(s): SMCJ followed by 5.0, 6.0, 6.5, 7.0, 7.5, 8.0, 8.5, 9.0, 10, 11, 12, 13, 14, 15, 16, 17, 18, 20, 22, 24, 26, 28, 30, 33, 36, 40, 43, 45, 48, 51, 54, 58, 60, 64, 70, 75, 78, 85, 90, 100, 110, 120, 130, 150, 160, 170, 180, 190, 200, 210, 220, 250, 300, 350, 400, or 440, followed by A or CA.

Transient Voltage Suppressor, Surface Mount Type, Model(s): SMDJ followed by 5.0, 6.0, 6.5, 7.0, 7.5, 8.0, 8.5, 9.0, 10, 11, 12, 13, 14, 15, 16, 17, 18, 20, 22, 24, 26, 28, 30, 33, 36, 40, 43, 45, 48, 51, 54, 58, 60, 64, 70, 75, 78, 85, 90, 100, 110, 120, 130, 150, 160, 170, 180, 190, 200, 210, or 220, followed by A or CA

Last Updated on 2024-04-17

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2024 UL LLC."